				, I
		SECRET		AND I
w	CLASSIFICATION	DECIM		50X1-HUI
	CENTRAL INTELLI	GENCE AGENCY	REPORT	33,111.01
	INFORMATION INFORMATION DOCUMENTS O	ON FROM OR RADIO BROADCASTS	CD NO.	
COUNTRY	USSR		DATE OF INFORMATION 1949 - 19	50
SUBJECT	Economic; Technological - M	Machine tools	IM ORDINATION 25 15	•
HOW PUBLISHED	Monthly periodical		DATE DIST. 5 Jan 1951	
WHERE PUBLISHED	Moscow		NO. OF PAGES 5	o
DATE PUBLISHED	Oct 1950		SUPPLEMENT TO	
LANGUAGE	Russian		REPORT NO.	
OF THE UNITED ST	AINS INFORMATION AFFICING THE NATIONAL DIFFMSE VIES WITHIN THE MEANING OF ESPIONAGE ACT SO AS AMERICED. ITS TRANSMISSION OR THE REVELLATION ANY RAMBER TO AR UNAUTHORIZED FERON IS PRO- EPRODUCTION OF THIS FORM IS PROMISITED.	THIS IS UNE	EVALUATED INFORMATION	
SOURCE	Vestnik mashinostroyeniya	, No 10, 1950	,	
.ooonqr	- CB VILLE MADILLESS OF G. SELLY	• • • • •	•	
*	writ munio	OF SOVIET MACHINE TOOL	ıs	
	PRODUCED :	IN 1949 - 1950		
. •	ı		D. A. Ryznkov	
				50X1-HU
				00/(11101
	INTU	ERSAL MACHINE TOOLS		
	ONLY.	EKOALI MOZINE		
	In June 1949, the Krasnyy pr	oletariy Plant convert	ed production of the	
Model	1A62 screw-cutting lathe to	oletariy Plant convert conveyer methods Th	ed production of the is modernized	
Model versi	on of the DIP-200.	conveyer meanage	machined on this lathe	
Model versi at a	1A62 screw-cutting lathe to on of the DiP-200. Parts having a diameter of l speed of 360 meters per minu	.00 millimeters can be te and parts having la	machined on this lathe rger diameters at even	
Model versi at a highe	1A62 screw-cutting lathe to on of the DiP-200. Parts having a diameter of 1 speed of 360 meters per minu r speeds. Modern improvemen	.00 millimeters can be te and parts having la ts making work at high	machined on this lathe rger diameters at even speeds possible and m incorporated into the	
Model versi at a highe provi	on of the DIP-200. Parts having a diameter of l speed of 360 meters per minur speeds. Modern improvementing greater convenience of	00 millimeters can be te and parts having lats making work at high speed control have bee	machined on this lathe rger diameters at even a speeds possible and in incorporated into the the length of work	
Model versi at a highe provi desig machi sitat	1A62 screw-cutting lathe to on of the DiP-200. Parts having a diameter of l speed of 360 meters per minur speeds. Modern improvementing greater convenience of this machine. A dial coned. Previously, this was med machine-tool stoppage.	00 millimeters can be te and parts having lasts making work at high speed control have been the apron indicates measured by a worker wi	machined on this lathe rger diameters at even speeds possible and in incorporated into the the length of work th a rule which neces-	50X1-HU I
Model versi at a highe provi desig machi sitat	1A62 screw-cutting lathe to on of the DiP-200. Parts having a diameter of l speed of 360 meters per minur speeds. Modern improvementing greater convenience of mof this machine. A dial coned. Previously, this was med machine-tool stoppage. In 1949, the Krasnyy proleta	00 millimeters can be te and parts having la its making work at high speed control have been the apron indicates measured by a worker with the speed control to a worker with the speed control to the	machined on this lathe rger diameters at even a speeds possible and an incorporated into the the length of work th a rule which necestains and at werful, high-speed Model	50X1-HU I
Model versi at a highe provi desig machi sitat	1A62 screw-cutting lathe to on of the DiP-200. Parts having a diameter of l speed of 360 meters per minur speeds. Modern improvementing greater convenience of m of this machine. A dial conded. Previously, this was maded machine-tool stoppage. In 1949, the Krasnyy proletation of the producing in series the contraction of the contract	00 millimeters can be te and parts having la ts making work at high speed control have been the apron indicates measured by a worker with the highly universal, por highly unive	machined on this lathe rger diameters at even a speeds possible and in incorporated into the the length of work the rule which necestimental models and at overful, high-speed Model to lathe has a stepless	50X1-HUI
Model versi at a highe provi desig machi sitat prese 1620 adju	1A62 screw-cutting lathe to on of the DiP-200. Parts having a diameter of l speed of 360 meters per minur speeds. Modern improvementing greater convenience of mof this machine. A dial coned. Previously, this was med machine-tool stoppage. In 1949, the Krasnyy proleta series is producing in series the screw-cutting lathe of origination of spindle speeds range.	00 millimeters can be te and parts having lats making work at high speed control have been the apron indicates to a worker with the apron indicates arily Plant built experience highly universal, points of the promise from 18 to 3,000 in the promise from 18 to 3 to	machined on this lathe riger diameters at even a speeds possible and in incorporated into the the length of work the a rule which necestimental models and at overful, high-speed Model the lathe has a stepless evolutions per minute.	50X1-HU I
Model versi at a highe provi desig machi sitat prese 1620 adju	lA62 screw-cutting lathe to on of the DiP-200. Parts having a diameter of l speed of 360 meters per minur speeds. Modern improvementing greater convenience of mof this machine. A dial coned. Previously, this was med machine-tool stoppage. In 1949, the Krasnyy proleta series to producing in series the screw-cutting lathe of originate of spindle speeds range machine 100-millimeter diameter diamet	00 millimeters can be te and parts having lats making work at high speed control have been the apron indicates to the apron indicates to the apron indicates to the apron indicates to the apron indicates are possible to the part of the highly universal, points of the parts at a speed make and make the parts at a speed to the par	machined on this lathe riger diameters at even a speeds possible and in incorporated into the the length of work the a rule which necestmental models and at overful, high-speed Model he lathe has a stepless evolutions per minute. If of up to 900 meters per are conveniently located	50X1-HUI
Model versi at a highe provi desig machi sitat prese 1620 adju It cominu	lA62 screw-cutting lathe to on of the DiP-200. Parts having a diameter of l speed of 360 meters per minur speeds. Modern improvementing greater convenience of mof this machine. A dial cond. Previously, this was med machine-tool stoppage. In 1949, the Krasnyy prolets strew-cutting lathe of originating in series the screw-cutting lathe of originating machine 100-millimeter diameter. The levers are few in minus on the strew of the screw are few in minus on the strew of the screw are few in minus on the strew of the screw are few in minus on the strew of the screw of the s	00 millimeters can be te and parts having lasts making work at high speed control have been the apron indicates measured by a worker with the highly universal, points from 18 to 3,000 rameter parts at a speed umber and push buttons	machined on this lathe rger diameters at even a speeds possible and an incorporated into the the length of work the a rule which necestmental models and at overful, high-speed Model are lathe has a stepless revolutions per minute. If of up to 900 meters per are conveniently located local qualities, excels	50X1-HU I
Model versi at a highe provi desig machi sitat prese 1620 adju It cominu	Parts having a diameter of 1 speed of 360 meters per minur speeds. Modern improvement ding greater convenience of this machine. A dial of med. Previously, this was med machine-tool stoppage. In 1949, the Krasnyy prolets ent is producing in series the screw-cutting lathe of originations of spindle speeds range and machine 100-millimeter diete. The levers are few in machine-tool control. This meaning lathes of spread of the screw-cutting lathes of spindle speeds range and machine-tool control. This meaning is the screw-cutting lathes of spindle speeds range and spindle spindle speeds range and spindle spind	00 millimeters can be te and parts having lasts making work at high speed control have been the apron indicates measured by a worker with the highly universal, points from 18 to 3,000 rameter parts at a speed umber and push buttons	machined on this lathe rger diameters at even a speeds possible and an incorporated into the the length of work the a rule which necestmental models and at overful, high-speed Model are lathe has a stepless revolutions per minute. If of up to 900 meters per are conveniently located local qualities, excels	50X1-HUI 50X1-HUM
model versi at a highe provi desig machi sitat prese 1620 adjui It ca minu for i	Parts having a diameter of 1 speed of 360 meters per minur speeds. Modern improvement ding greater convenience of this machine. A dial of med. Previously, this was med machine-tool stoppage. In 1949, the Krasnyy prolets ent is producing in series the screw-cutting lathe of originations of spindle speeds range and machine 100-millimeter diete. The levers are few in machine-tool control. This meaning lathes of spread of the screw-cutting lathes of spindle speeds range and machine-tool control. This meaning is the screw-cutting lathes of spindle speeds range and spindle spindle speeds range and spindle spind	00 millimeters can be te and parts having lasts making work at high speed control have been the apron indicates measured by a worker with the highly universal, points from 18 to 3,000 rameter parts at a speed umber and push buttons	machined on this lathe rger diameters at even a speeds possible and an incorporated into the the length of work the a rule which necestmental models and at overful, high-speed Model are lathe has a stepless revolutions per minute. If of up to 900 meters per are conveniently located local qualities, excels	
model versi at a highe provi desig machi sitat prese 1620 adjui It ca minu for i	Parts having a diameter of 1 speed of 360 meters per minur speeds. Modern improvement ding greater convenience of this machine. A dial of med. Previously, this was med machine-tool stoppage. In 1949, the Krasnyy prolets ent is producing in series the screw-cutting lathe of originations of spindle speeds range and machine 100-millimeter diete. The levers are few in machine-tool control. This meaning lathes of spread of the screw-cutting lathes of spindle speeds range and machine-tool control. This meaning is the screw-cutting lathes of spindle speeds range and spindle spindle speeds range and spindle spind	00 millimeters can be te and parts having lasts making work at high speed control have been the apron indicates measured by a worker with the highly universal, points from 18 to 3,000 rameter parts at a speed umber and push buttons	machined on this lathe rger diameters at even a speeds possible and an incorporated into the the length of work the a rule which necestmental models and at overful, high-speed Model are lathe has a stepless revolutions per minute. If of up to 900 meters per are conveniently located local qualities, excels	
model versi at a highe provi desig machi sitat prese 1620 adjui It ca minu for i	Parts having a diameter of 1 speed of 360 meters per minur speeds. Modern improvement ding greater convenience of this machine. A dial of med. Previously, this was med machine-tool stoppage. In 1949, the Krasnyy prolets ent is producing in series the screw-cutting lathe of originations of spindle speeds range and machine 100-millimeter diete. The levers are few in machine-tool control. This meaning lathes of spread of the screw-cutting lathes of spindle speeds range and machine-tool control. This meaning is the screw-cutting lathes of spindle speeds range and spindle spindle speeds range and spindle spind	00 millimeters can be te and parts having lasts making work at high speed control have been the apron indicates measured by a worker with the highly universal, points from 18 to 3,000 rameter parts at a speed umber and push buttons	machined on this lathe rger diameters at even a speeds possible and an incorporated into the the length of work the a rule which necestmental models and at overful, high-speed Model are lathe has a stepless revolutions per minute. If of up to 900 meters per are conveniently located local qualities, excels	
model versi at a highe provi desig machi sitat prese 1620 adjui It ca minu for i	Parts having a diameter of 1 speed of 360 meters per minur speeds. Modern improvement ding greater convenience of this machine. A dial of med. Previously, this was med machine-tool stoppage. In 1949, the Krasnyy prolets ent is producing in series the screw-cutting lathe of originations of spindle speeds range and machine 100-millimeter diete. The levers are few in machine-tool control. This meaning lathes of spread of the screw-cutting lathes of spindle speeds range and machine-tool control. This meaning is the screw-cutting lathes of spindle speeds range and spindle spindle speeds range and spindle spind	00 millimeters can be te and parts having lasts making work at high speed control have been the apron indicates measured by a worker with the highly universal, points from 18 to 3,000 rameter parts at a speed umber and push buttons	machined on this lathe rger diameters at even a speeds possible and an incorporated into the the length of work the a rule which necestmental models and at overful, high-speed Model are lathe has a stepless revolutions per minute. If of up to 900 meters per are conveniently located local qualities, excels	
model versi at a highe provi desig machi sitat prese 1620 adjui It ca minu for i	Parts having a diameter of 1 speed of 360 meters per minur speeds. Modern improvement ding greater convenience of this machine. A dial of med. Previously, this was med machine-tool stoppage. In 1949, the Krasnyy prolets ent is producing in series the screw-cutting lathe of originations of spindle speeds range and machine 100-millimeter diete. The levers are few in machine-tool control. This meaning lathes of spread of the screw-cutting lathes of spindle speeds range and machine-tool control. This meaning is the screw-cutting lathes of spindle speeds range and spindle spindle speeds range and spindle spind	00 millimeters can be te and parts having lats making work at high speed control have been the apron indicates measured by a worker with the highly universal, point from 18 to 3,000 remeter parts at a speed imber and push buttons machine, in its operation its size produced by	machined on this lathe rger diameters at even a speeds possible and in incorporated into the the length of work the a rule which necestimental models and at werful, high-speed Model a lathe has a stepless revolutions per minute. In it is of up to 900 meters per are conveniently located lonal qualities, excels soviet plants or foreign	
model versi at a highe provi desig machi sitat prese 1620 adjui It co minu for i	Parts having a diameter of 1 speed of 360 meters per minur speeds. Modern improvement ding greater convenience of this machine. A dial of med. Previously, this was med machine-tool stoppage. In 1949, the Krasnyy prolets ent is producing in series the screw-cutting lathe of originations of spindle speeds range and machine 100-millimeter diete. The levers are few in machine-tool control. This meaning lathes of spread of the screw-cutting lathes of spindle speeds range and machine-tool control. This meaning is the screw-cutting lathes of spindle speeds range and spindle spindle speeds range and spindle spind	00 millimeters can be te and parts having lats making work at high speed control have been the apron indicates measured by a worker with the highly universal, point from 18 to 3,000 remeter parts at a speed imber and push buttons machine, in its operation its size produced by	machined on this lathe rger diameters at even a speeds possible and an incorporated into the the length of work the a rule which necestmental models and at overful, high-speed Model are lathe has a stepless revolutions per minute. If of up to 900 meters per are conveniently located local qualities, excels	

SE	r	579		7	
υe	(4	20	ħ.		

SECRET

50X1-HUM

The Middle Volga (Srednevolzhskiy) Machine-Tool Building Plant has begun series production of the new Model 1616, 160-millimeter-swing screw-cutting lathe, the spindle speeds and capacity of which are double those of Model 1615M. Parts having an 80-millimeter diameter can be machined at a speed of up to 500 meters per minute. Machine-tool control is exceptional for its simplicity and convenience.

50X1-HUM

The Gor'kiy Milling Machine Plant has undertaken production of five new models of knee-type milling machines: 6N82 universal, 6N82G horizontal, 6N12 vertical, 6N83G horizontal and 6N13 vertical. The milling sneed on these machines reaches 600 meters per minute and higher.

50X1-HUM

The Odessa Radial Drilling-Machine Plant has undertaken series production of a new heavy-duty radial drilling machine, Model 257, for drilling up to 75-millimeter-diameter holes. The speeds and feeds of this machine are controlled hydraulically by means of a hand lover. It is provided with automatic feed disengagement when drilling to a specified depth.

The Leningrad Plant imeni Sverdlov has manufactured an experimental model of a horizontal boring machine with a 125-millimeter spindle diameter. A photograph of this machine appears on the cover of Vestnik mashinostroveniya, No 6, 1950. /Identified as Model 2631 in the issue cited. It is exceptional for its rigidity, vibration resistance, high precision, and high finishing properties. There are no hand wheels on the machine; all controls are by push button.

50X1-HUM

In addition to increased productivity, these universal machine tools have been designed with principles of accident prevention and improved working conditions in mind.

SPECIAL AND COMBINATION MACHINE TOOLS AND AUTOMATIC TRANSFER LINES

The Krasnyy proletariy Plant has begun production of a series of special high-speed lathes for chuck or center work. These include Models MK-163, MK-164, MK-167, MK-182, and MK-185. These machines are designed for high-speed cutting, exceeding 1,600 meters per minute; they are at least four times more productive than previous models.

This plant has also begun production of a unique heavy machine tool, Model 9801, weighing 35 tons, for finish and semifinish turning of up to 450-millimeter-diameter crankpins and webs on 5,000-millimeter-long crankshafts. The oval and tapered parts of the shaft webs can be machined to a tolerance of G.005-0.015

For the first time in the Soviet Union, the Krasnyy proletariy Plant has put into product on a two sition hydraulic multicutter semiautomatic, Model 1841. weighing 32 tons, i cended for simultaneous machining of all crankpins on two automobile crankshafts. It machines to high precision and is twice as productive as the existing models at automobile and tractor plants. The only operations which the operator must perform are installation and removal of the work and starting the machine.

This plant has also put in production an original high-duty thread-milling automatic, Model MK-191, for simultaneous hole and face milling and threading of two ends of a graphite electrode having a 225-500 millimeter diameter and 1,500-millimeter length. The machining cycle, loading, and unloading are completely automatic. All friction surfaces of the machine are hermetically sealed; the

- 2 -

SECRET

SEGNET

Sanitized Copy Approved for Release 2011/09/27 : CIA-RDP80-00809A000600370266-6

ţ	F	n	7	د! ديا	7	

SECRET

50X1-HUM

cutting process is carried out in special housings from which the graphite dust is removed through an exhaust device. This assures sanitary and hygienic work conditions and long life of the automatic's mechanisms.

The Leningrad Plant imeni Sverdlov is now producing a heavy universal four-spindle horizontal boring machine, Model IR-10, weighing 175 tons, for simultaneous high-speed bilateral boring of piston and valve holes in locomotive cylinders, and turning the ends adjacent to the holes. Its high rigidity and vibration resistance makes machining at a rate of up to 400 meters per minute possible, which, in comparison with similar machines of foreign firms, gives a productivity of eight to ten times greater. The design of the machine eliminates the use of interchangeable boring bars, which considerably eases the work of the operator and shortens the time required for auxiliary operations.

This plant has also undertaken production of a two-spindle LR-15 machine for boring and undercutting the faces for crank pins on locomotive wheel pairs. In comparison with analogous machine tools of foreign firms, the productivity of the new machine, which is up to ten wheel pairs per shift, is four to eight times as great, while the requirements for operating personnel are only half as great.

During recent years, the field for using combination machine tools has broadened considerably. Where earlier they were manufactured mainly for the automobile and tractor industry, at present, a large number of them are being built for agricultural machine-building, the electrical industry, and other plants.

The Plant imeni Ordzhonikidze has manufactured machine tools for st aight-line production of resper frames and mower frames for the Lyubertsy Agricultural-Machine Building Plant. One machine, Model 1A285, operating in a line for machining mower frames, bores two holes having a diameter of 61.4 millimeters and drills six holes having a diameter of 6.7-11 millimeters. Its productivity is 20 frames per hour.

Milling machines are now being manufactured from standard units. A large number of these milling machines have been built especially for the Automobile Plant imeni Stalin such as the Model 1A319 for milling front axles for the ZIS-150 truck.

The automatic transfer machine-tool line, 1A58-1A78, designed by the SKB-1 /Machine-Tool Design Bureau No 1/2 and manufactured by the Stankokonstruktsiya Plant, is intended for machining Diesel cylinder blocks at the Yaroslavl' Automobile Plant. It performs the following operations: drilling, counterboring, removing chamfered edges, and cutting threads in the upper and lover surfaces of the cylinder block on the supercharger side. The blocks are transferred from one position to another by means of a bar actuated by a hydraulic cylinder.

When the work is transferred from one section of the line to the next, it is automatically turned, fixed, and locked in all working positions by pneumatic-hydraulic power.

The line consists of 22 machine tools with a total of 351 simultaneously operating spindles and 38 electric motors having a total power of 113 kilowatts. Four workers service the line; its productivity is 20 blocks per hour. If these blocks were machined on universal machine tools, 24 skilled workers would be required.

The 1A443-1A448 automatic transfer machine-tool line, designed by the SKB-1 and manufactured by the Moscow Plant imeni Ordzhonikidze, is intended for drilling, removing chamfered edges, facing bosses, boring, reaming, and cutting threads in oblique holes under the distributor and oil pump in the four-cylinder automobile engine block.

- 3 -

SECRET

SECRET



SECRET

50X1-HUM

The line consists of six double-sided sloping machine tools with two-position attachments and a total of 60 spindles. The 22 electric motors have a total power of 50.8 kilowatts. The line is equipped with attachments for automatically controlling the depth of holes, a special automatic (exice for servolubrication of taps, and a chip removal mechanism and conveyer.

Compressed air is used for cleaning chips from holes. The line is controlled automatically by a servomechanism. The central control panel is provided with a device for rapid detection of incipient trouble spots.

Labor consumption in machining a block on the line is 18 times less than on universal machines, and five times less than on combination machine tools.

An example of the highly automatic productive process is the automatic plant which was developed by scientific organizations and plants of the Ministry of Machine-Tool Building for manufacturing aluminum pistons for the ZIS-150 and GAZ-MM. At this plant, the entire work cycle is automatic, beginning with the casting and ending with the packing of completed pistons. All deviations from the specified work regime are noted by signals. It is the duty of the servicing personnel to remedy defects and take preventive measures as a precaution against breakdown of the units.

This work is done outside of working hours, and on the third shift.

TOOL AND ABRASIVE PRODUCTION

The experience of innovators in high-speed machining and the development of machine tools for working at high speeds has pushed to the fore the need fordeveloping a full range of tool types and expanding hard-alloy tool production.

The range of types of hard alloy tools such as drills, counterbores, reamers, facing disks and end mills increased 2.5 times in 1949 as compared with 1948.

Series production has begun on (a) large-module sectional hobs, Grade A hobs, precision-made milling cutters for precision machine building; hobs, gear cutters, and shavers of 0.3-1 millimeter module for instrument building; (b) threading and boring tools for machining pipes up to 16 inches in diameter, and 3KA and 4KA threading dies for automatics.

A number of measuring-tool plants are now series producing complex checking automatics for piston rings and ball bearings, electric multimeasuring instruments of the signal-light type, two-tube air gauges, instruments for checking play in small-module gears with minimeters of new design, and checking-and-sorting automatics.

Achievements in abrasive production have made possible the cessation of imports of abrasive tools. During 1949, Soviet industry received 94 new types of improved-quality abrasive tools from the domestic abrasive industry.

The industrial application of the VNIIASh (All-Union Scientific Research Institute for Abrasives and Grinding) technology in the production of special abrasive tools for truing grinding wheels is important. Plants of the Main Administration of the Abrasives Industry have developed an abrasive material called monocorundum which replaces diamonds. This new material has increased labor productivity 25-35 percent.

-14-

SECRET

SECRET

Sanitized Copy Approved for Release 2011/09/27: CIA-RDP80-00809A000600370266-6

SECOLI

SECRET

50X1-HUM

NEW TECHNOLOGY

The Moscow Krasnyy proletariy Plant's DiP-200 lathe and the Middle Volga Plant's 1615 lathe were the first in world machine-tool building to be manufactured on a straight-line conveyer basis. Without stopping the production of the DiP-200 lathe, the Krasnyy proletariy Plant converted to conveyer production of its modernized 1A62 high-speed lathe, while the Middle Volga Plant converted to production of the 1615M lathe.

At present, more than 90 percent of lathes having a 320-400 millimeter swing are produced by conveyer methods at plants of the Ministry of Machine-Tool Building USSR. As a result, labor consumption for the manufacture of machine tools has decreased 25-30 percent and production has increased 40-50 percent.

The Soviet tool industry was also the first in the world to set up assembly conveyer and machining conveyer production of micrometers and slide rules (Kalibr Plant), dies and taps (Frezer, Sestroretsk, and other plants) and segments for circular saws (Kirzhach Plant).

At abrasive plants, conveyer lines have been put into operation for the production of bakelite-bond grinding wheels. Labor consumption is cut 15 percent.

FUTURE MODELS

A number of precision machine tools must be developed in the near frture. The fulfillment of this assignment will require a concerted effort on the part of all machine-tool building personnel.

The number of types of gear-machining machine tools must be increased. New models are needed for precision machine building and heavy machine building. Machine tools for cutting gears having globoid meshing must be put into production.

Heavy boring machines must also be developed.

- E N D -

- 5 -

SECRET

SECRET